

ALUMINUM SILVER STAR TAG-A-LONG 5' & 6'W

SPECIFICATIONS	SSAC58SA	SSAC510SA	SSAC610SA	SSAC612SA
AXLES/SPRING	2990#	2990#	2990#	2990#
TIRES	15" RADIAL	15" RADIAL	15" RADIAL	15" RADIAL
BRAKES	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL
TUBE FRAME	3"	3"	3"	3"
HITCH BALL SIZE	2"	2"	2"	2"
CURB WEIGHT**	962#	1121#	1130#	1235#
HITCH WEIGHT	125#	146#	147#	161#
GVWR	2990#	2990#	2990#	2990#
PAYLOAD CAPACITY	2028#	1869#	1860#	1755#
OVERALL LENGTH	12'-2"	14'-2"	14'-2"	16'-2"
OVERALL WIDTH	6'-8"	6'-8"	7'-8"	7'-8"
OVERALL HEIGHT	6'-8"	6'-8"	8'-2"	8'-2"
EXTERIOR BOX WIDTH	5'	5'	6'	6'
INTERIOR LENGTH W/V'	9'7"	11'7"	11'7"	13'7"
INTERIOR WIDTH	4'-9"	4'-9"	5'-9"	5'-9"
INTERIOR HEIGHT	60-1/4"	60-1/4"	78-1/4"	78-1/4"
PLATFORM HEIGHT	19"	19"	19"	19"
RAMP REAR DOOR***	LT DUTY	LT DUTY	LT DUTY	LT DUTY
REAR DOOR WIDTH	4'-2"	4'-2"	5'-4"	5'-4"
REAR DOOR HEIGHT	4'-5"	4'-5"	6'-1"	6'-1"
SIDE DOOR WIDTH	N/A	N/A	32"	32"
SIDE DOOR HEIGHT	N/A	N/A	70"	70"
CROSS MEMBERS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
WALL POSTS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
ROOF MEMBERS O.C.	24"O.C.	24"O.C.	24"O.C.	24"O.C.

* ADDING ELECTRIC BRAKES TO 5'W OR 6'W CHANGES GVWR TO 3500#

Curb weights are based on STD model with no options

***Light Duty Ramp Door (No Flap) is the New Standard on 5' & 6'W Models. Double Cargo Doors may be
Optioned at No Charge.