

## TAG-A-LONG

### STAR 6'W

SPECIFICATIONS	ST610SA	ST612SA	ST612TA2	ST614TA2
AXLES/SPRING	2990#	2990#	3500#	3500#
TIRES	15" RADIAL	15" RADIAL	15" RADIAL	15" RADIAL
BRAKES	OPTION	OPTION	ELECTRIC	ELECTRIC
TUBE FRAME	3" TUBE	3" TUBE	4" TUBE	4" TUBE
HITCH BALL SIZE	2"	2"	2-5/16"	2-5/16"
CURB WEIGHT	1177#	1339#	1759#	1940#
HITCH WEIGHT	159#	181#	237#	262#
GVWR	2990#	2990#	7000#	7000#
PAYLOAD CAPACITY	1813#	1651#	5241#	5060#
OVERALL LENGTH	14'-2"	16'-2"	16'-2"	18'-2"
OVERALL WIDTH	7'-8"	7'-8"	7'-8"	7'-8"
OVERALL HEIGHT	8'-2"	8'-2"	8'-3"	8'-3"
EXTERIOR BOX WIDTH	6'	6'	6'	6'
INTERIOR LENGTH	10'-2"	12'-2"	12'-2"	14'-2"
INTERIOR WIDTH	5'-8"	5'-8"	5'-8"	5'-8"
INTERIOR HEIGHT	6'-7"	6'-7"	6'-7"	6'-7"
PLATFORM HEIGHT	18"	18"	19"	19"
REAR DOORS	DOUBLE	DOUBLE	DOUBLE	DOUBLE
REAR DOOR WIDTH	5'-3"	5'-3"	5'-3"	5'-3"
REAR DOOR HEIGHT	6'	6'	6'	6'
SIDE DOOR WIDTH	32"	32"	32"	32"
SIDE DOOR HEIGHT	70"	70"	70"	70"
CROSS MEMBERS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
WALL POSTS O.C.	16"O.C.	16"O.C.	16"O.C.	16"O.C.
ROOF MEMBERS O.C.	24"O.C.	24"O.C.	24"O.C.	24"O.C.

\*\*Adding electric brakes changes GVWR to 3500#\*\*